SUNWARD AMERICA™

Attachment Guide

SWC Series Hydraulic Hammer

Model	SC200-2-Silent Breaker	SC2200A_HD Breaker	SC400-Silent Breaker	SC450 -Silent Breaker	SC800-2-Silent Breaker	SC2200A-Silent Breaker	SC3500F_HD Breaker
Machine	SWE25F/25UF	SWE215F	SWE60UF	SWE90UF	SWE155F	SWE215F	SWE365F
Body Weight (Lbs)	156	2107	344	622	1056	2107	3504
Total weight (Lbs)	284.316	3987.036	795.644	1615.532	2219.428	4509.384	7222.508
Length (inch)	52.4015748	97.63779528	65.35433071	81.65354331	92.67716535	109.9606299	111.023622
Width (inch)	10.23622047	22.63779528	15.15748031	18.03149606	18.03149606	22.63779528	26.18110236
Height (inch)	11.61417323	52.55905512	19.13385827	22.44094488	22.44094488	27.95275591	56.88976378
Operating Pressure (psi)	1280-1704	2272-2556	1562-1988	1846-2272	2130-2414	2272-2556	2417-2844
HD flow range (Gallon per	5-8	31-48	10-19	15-27	26-29	31-48	52-66
Impact Frequency	700-1200	350-500	500-900	400-800	350-700	350-500	250-380
Diameter of hose(inch)	0.5	1	0.5	0.75	0.75	1	1.25
Diameter of Tool(inch)	1.771653543	5.511811024	2.677165354	3.346456693	3.937007874	5.511811024	6.496062992
weight of tool (Lbs)	17.632	297.54	39.672	63.916	125.628	297.54	473.86
Suitable carrier (Ton)	.8-2.5	18-26	4-7	7-14	15-18	18-26	30-40
Accumulator	No	Yes	No	No	No	Yes	Yes

Precision Machining

CAE Designing technology allows for precision engineering

Robust Manufacturing

High-Quality metals allow for robust engineering standards

Computerized Process

Powered by an advanced computer algorithm, Sunward can guaranteee perfect manufacturing accuracy

(469)-353-6890 **sunwardamerica**.com

Sunward machine names, colors schemes, and corporate and product identities used within this booklet are all are all Trademarks of Sunward America Corp. The information within this booklet is for informational purposes only, and any specifications, deals, models, and names are subject to change without warning from Sunward America Corp.